

Swimming Pool Slotted Drains

SLKN 01, SLKN 02



Characteristics:

CHANNEL

- material CrNi 18/10 (AISI -304) or CrNi 17/12 (AISI-316L), thickness 1,2 mm
- length 2000, 4000 mm; different lengths could be made to order
- ruff around the channel for connection to hydro-isolation
- mounting legs with M10 screws for better seating of the channel to the floor (horizontal position)
- bond screw for connection with bonding conductor
- gradient of the channel: 1 cm on 1 m

WASTE OUTLET

- Ø 50 mm, rate of flow 20 l/min (atypical dimensions could be made to order)
- easy to clean, with a stink trap
- max. one water outlet in 4 meters long channel

GRID

- material CrNi 18/10 (AISI -304) or CrNi 17/12 (AISI-316L), thickness 1,2 mm
- brushed finish (polished finish for additional charge)
- dimensions of the hole 5 x 50 mm (width x length)
- safe for children

Supply Specification:

- SLKN 01** – supply No. **69010** AISI-304 stainless steel slotted drain (2 m); stainless steel waste outlet with a stink trap, grid
- SLKN 02** – supply No. **69020** AISI-304 stainless steel slotted drain (4 m); stainless steel waste outlet with a stink trap
- SLKN 01L** – supply No. **69017** AISI-316L stainless steel slotted drain (2 m); stainless steel waste outlet with a stink trap
- SLKN 02L** – supply No. **69027** AISI-316L stainless steel slotted drain (4 m); stainless steel waste outlet with a stink trap

Dimensions:

