

Other Accessories



SLA 01 - supply No. 06010
battery Extreme Life 9V/1900 mAh, battery life 20 years at 250 uses per day

SLA 02 – supply No. 06020
inlet fitting with a rubber seal for the urinals with back water inlet

SLA 04 – supply No. 06040
plastic connection with a rubber seal between flushing unit and urinal with back water inlet

SLA 09 – supply No. 06090
lithium battery 9V/1200 mAh, type U9VL

SLA 10 – supply No. 06100
stainless steel sieve for urinal Nova

SLA 11 – supply No. 06110
universal plastic sieve for urinals

SLA 17 – supply No. 06170
chromium-plated vandal-proof shower head

SLA 18 – supply No. 06180
universal plastic sieve with a Fresh Air filling for urinals

SLA 19 – supply No. 06190
set (12 pcs.) of Fresh Air fillings for SLA 18

SLA 26 – supply No. 06260
stainless steel sieve for urinal GOLEM

SLA 28 – supply No. 06280
chromium-plated shower head

SLA 29 – supply No. 06290
alkaline battery 9V/550 mAh, type 6F22

SLA 30 – supply No. 06300
reflexive foil for SLP 05K/KZ

SLA 36 – supply No. 06360
set of alkaline batteries, 4 pcs. 1.5V AA 2700 mAh

SLA 39 - supply No. 06390
vandal-proof shower head; material: brass/chrome; water inlet: 1/2"; rate of flow: 9 l/min

SLA 40 - supply No. 06400
vandal-proof shower head, possibility to set an angle of water flow in range 45°, material: brass/chrome; water inlet: 1/2"; rate of flow: 9 l/min

SLD 03 – supply No. 07030
universal remote control for an adjustment of parameters of all products with infra-red sensor, operating voltage 6V DC, reach approx. 20 cm

SLD 04 – supply No. 07040
remote control for an adjustment of parameters of radar flushing units and piezo controls, operating voltage 6V DC, reach approx. 5 cm

SLD 05 – supply No. 07050
remote control for an adjustment of parameter of coin shower timers

SLT 04 – supply No. 09040
¾" automatic thermostatic mixing valve, rate of flow 28 l/min by 0,1 MPa pressure, temperature of water is adjusted within the range 35 - 65°C, for the right function of mixture valve the pressure of water have to be the same on the both water inlets, there have to be installed non-returned valves in the front of water inlets

SLT 05 – supply No. 09050
½" automatic thermostatic mixing valve with a safety fuse on 38°C, rate of flow 42 l/min by 0,1 MPa pressure, temperature of water is adjusted within the range 15 - 50°C, for the right function of mixture valve the pressure of water have to be the same on the both water inlets, there have to be installed non-returned valves in the front of water inlets

SLT 07 – supply No. 09070 (43 l/min, 3/4")

SLT 08 – supply No. 09080 (53 l/min, 1")

SLT 09 – supply No. 09090 (82 l/min, 5/4")

SLT 10 – supply No. 09100 (155 l/min, 6/4")
automatic thermostatic mixing valve, rate of flow by 0,1 MPa pressure, water temperature adjusted within the range 25 - 50°C, for the right function of mixture valve the pressure of water have to be the same on the both water inlets, there have to be installed non-returned valves in the front of water inlets

SLA 37 – supply No. 06370
cleaner for stainless steel products